

Clean Dry Air Packages

Altec AIR's Clean Dry Air Package is a complete, enclosed, compact unit, consisting of an Oil-less Air Compressor, Regenerative Desiccant Air Dryer, Regulator, Coalescing and Particulate Filters. This packages is great for applications requiring low volumes of clean, dry compressed air at pressures up to 75 PSIG.



- Reliable oil-less Compressor to assure oil-free air at all times.
- Equipped with Rocking Piston Pump technology for long interval times between maintenance and easy service.
- Proven Regenerative Desiccant Heatless Air Dryer uses dual tower technology for continuous dry air supply.

	CDA10	CDA10-2
Output Capacity	Normal: 5 LPM Continuous Maximum: 10 LPM Emergency	
Power Requirements (15 Amp Service Recommended)	115 VAC, 1 Phase, 50/60 Hz	230 VAC, 1 Phase 50/60 Hz
Outlet Pressure Range	0 - 75 PSIG (0 - 5.1 bar)	
Outlet Dewpoint	-100°F (-73°C) Atmospheric Dewpoint	
Compressor Type	1/3 HP, Oil-less, Rocker Piston	
Dehydrating Method	Heatless Desiccant	
Environment Operating Temperature Range	Minimum: 33°F (1°C) Optimal: 70°F (21°C) Maximum: 120°F (49°C)	
Outlet Connection	1/4" NPT x 1/4" Press-to-Lock Tube Fitting	
Drain Connection	1/4" NPT x 3/8" Press-to-Lock Tube Fitting	
Dimensions	18" D x 24" W x 14" H (45.7 cm D x 61.0 cm W x 35.6 cm H)	
Weight	72 lbs (32.7 kgs)	

SPECIFICATIONS & DIMENSIONS

For more complete information on Altec AIR products and services, visit us on the web at www.AltecAIR.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec AIR representative for all available options. Altec AIR logo is a registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission. © 2020 Altec AIR. All Rights Reserved. CDA-0520

