MODEL	RAD-1000A-4-D		
VOLTAGE	460V-3PH-60HZ		
RLA	9.3		
LRA	47.5		
MCA	9.5		
MOP	25		
COMPRESSOR HP	6		
COMPRESSOR	SCROLL		
REFRIGERANT	R449A		
REFRIGERANT CHARGE (OZ)	144		53.34
MAX INLET AIR TEMP (F)	140		9.65
MAX INLET AIR PRESSURE (PSI)	232		
MIN/MAX AMBIENT TEMP (F)	45/120		
REFRIGERANT PRESSURE RANGE (PSI)	181/450		16.08
INLET/OUTLET (NPT)	3		
WEIGHT (LB)	600		
	55.79 1/4 NP	AIR INLET AIR OUTLET	SUCTION PRESSURE GAUGE
		AIRFLOW CKURZ APPROVED - DATE 10 (20) (2022)	UNLESS OTHERWISE NOTED, TOLERANCES ARE: FRACTIONS: ±1/16 ANGLES: ±0*30' DECIMAL: .X = ±.06 .XX = ±.03 .XXX = ±.015 .XXXX = ±.0030 MACHINED SURFACES: 125 MICROINCHES THESE TOLERANCES DO NOT APPLY TO BASIC DIMENSIONS. DO NOT SCALE THIS PRINT, REMOVE ALL BURRS & SHARP
		MATERIAL MATERIAL	EDGES, ALL DIMENSIONS ARE IN INCHES. CAD SOFTWARE: SOLIDWORKS. DRAWING DIMENSIONED TO ALTEC STANDARD: CDS-0007.
		FINISH	CONFIDENTIAL: This drawing and its contents are the proprietary and confidential informatio of Altec Industries, Inc. and are not to be reproduced, copied or publicly disclosed. If this drawing is provided to someone outside Altec, it is done so for the limited purpose of assistin that recipient with a technical or product issue. In receiving this drawing, the recipient agrees to maintain it in confidence and not to use it beyond the purpose previously stated. Recipient agrees not to reproduce, copy, or publicly disclose this drawing and its contents.

