· · · · · · · · · · · · · · · · · · ·	•				
MODEL	RAD-1250A-4				
VOLTAGE	460V-3PH-60HZ		\wedge		
RLA	11.5				
LRA	63				
MCA	11.7		$\langle \langle \cdot \rangle$		T
	<u>30</u> 7				
COMPRESSOR HP				く ろう ろう ひょう ひょう ひょう ひょう ひょう ひょう ひょう ひょう ひょう ひょ	
	SCROLL				
	R449A				
	160 140				
MAX INLET AIR TEMP (F)					53.21
	232				12.01
MIN/MAX AMBIENT TEMP (F)	45/120				12.01
REFRIGERANT PRESSURE RANGE (PSI)	181/450				
	3				₽
WEIGHT (LB)	625				14.44
					T SUCTION PRESSURE GAUGE DISCHARGE GAUGE
	55.78 1/4 N	PT DRAIN PORT			
			AIRFLO	JVV J. GAMBL	E UNLESS OTHERWISE NOTED, TOLERANCES ARE: FRACTIONS: ±1/16 ANGLES: ±0°30'
				APPROVED	DECIMAL: X = ±.06 .XX = ±.03 .XXX = ±.015 .XXXX = ±.0030 MACHINED SURFACES: 125 MICROINCHES
				- DATE	THESE TOLERANCES DO NOT APPLY TO BASIC DIMENSIONS.
				02/03/202 MATERIAL	BORGES, ALL DIMENSIONS ARE IN INCHES.
					DRAWING DIMENSIONED TO ALTEC STANDARD: CDS-0007.
					TITLE: DRYR-REFRIG; NON-CYCL; 1250 SC
				FINISH	

