

| MODEL | UA1000A-4 | UA1000A-5 | |
|-------------------------------|-----------------|-----------------|--|
| VOLTAGE | 460VAC-3PH-60HZ | 575VAC-3PH-60HZ | |
| VOLTAGE RANGE | 414-506 | 483-667 | |
| RLA | 10 | 10 | |
| LRA | 52 | 52 | |
| MIN. CIRCUIT AMP | 14 | 14 | |
| MAX. FUSE SIZE | 20 | 20 | |
| MAX. INLET AIR TEMP - F | 110 | 110 | |
| MIN/MAX AMBIENT TEMP - F | 45/110 | 45/110 | |
| REF. SYSTEM DESIGN - PSIG | 181/450 | 181/450 | |
| SUCTION / DISCHARGE - PSIG | 70/225 | 70/225 | |
| ref. compressor hp | 6 | 6 | |
| REFRIGERANT TYPE | R404A | R404A | |
| REFRIGERANT CHARGE | 9 LBS | 9 LBS | |
| MAX AIR PRESSURE - PSIG | 232 | 232 | |
| INLET / OUTLET PORT - NPT | 3" NPT | 3" NPT | |



| mation his issisting ated. ents. | SCALE | WEIGHT | SIZE | NUMBER | REV |
|--|-------|--------|------|-----------|-----|
| | 1:20 | 141.9 | 2 | UA1000A-X | А |