

PPEC548 - Moisture Separator / Manual Dryer



- Easily and quickly serviced
- Color change of the desiccant provides an instant status of the compressed air system
- No power required
- Includes 1.6 lbs desiccant (Silica Gel)

P8525 - Pressure Shut Off Valve



This versatile indoor valve controls flow to an individual cable without blocking flow to adjacent valves or cables. Neoprene diaphragm (toggle actuated) bears against a smooth brass seat for positive closure.

PPEC725 - By-Pass Valve



Equipped with a shut off valve which is used for constructing a by-pass across a pressure plug using 3/8" O.D. plastic tubing.

- 3/8" O.D. tube fittings
- Brass/Tin or Cadmium Plated

PPEC506 - Valve Repair Tool



Multi-purpose design includes wrench to remove valve cores, tap and tread-cutting die to remove burrs from valve stem threads. Can be used to install valve into cable sheath.

Pressure Testing Hose



Designed to move gas from a pressure testing regulator to an inlet valve.

- Snap-on chuck
- 1/4" coupling

Part No.	Length
P08206	2.5'
PPEC507A	8'

Cable Buffering Hose & Kit



Used as a pneumatic jumper between the pipe valve and cable valve to provide a buffering pressure source to a cable during splicing activity

- Screw type chuck
- 5' long

Part No.
PPEC729 - Hose only
PPEC730 - Hose, 6 tags/ties

PPEC724A - Automatic Shut Off (Check) Valve



Designed for installation between air pipe and the manifold assembly to protect cable pressures when breakage or other damage to the feeder pipe threatens loss of pressure.

- 1/8" FTP port
- 1/8" MPT connector
- Brass/Tin or Cadmium Plated