

Nitrogen Bottle Replacement Module

Mobile Air



- Eliminate the need for costly nitrogen bottles
- Versatile applications - air tools, emergency dry air
- Equipped with a connection for use with pneumatic tools
- Locate easily in a slide-out or compartment tray in a truck or van
- Uses the vehicle power supply
- Conserve labor, energy, and storage costs
- Available in horizontal or stack configuration
- Chemical or regenerative heatless air dryers create dry air
- Compact size and portability for transferring between vehicles



P05860BASH



P05860GLTG



P05860H2

Specifications

	P05860BASH	P05860H2	P05860GLTG
Power Requirements	220 VAC, 1-Phase, 60 Hz	220 VAC, 1-Phase, 60 Hz	
Running Amps	8.5 Amps	10.6 Amps	
Air Compressor	Two-cylinder, oil-less type, 3/4 HP	Four-cylinder, oil-less type, 1.5 HP	
Outlet Pressure Range	80-110 PSIG	Dry Air: 0-30 PSIG Tool Air: 0-80 PSIG	80-110 PSIG
Ambient Operating Temperature Range	35° to 120°F (1.7° to 49°C)		40° to 95°F (4.5° to 35°C)
Drying Method	Heatless Desiccant		Silica Gel
Outlet Air Relative Humidity	Less than 2% RH at 70° F		
Dew Point	-40° F at atmospheric pressure		
Dimensions	12.5" W x 25.3" H x 39.3" L (32 cm x 64 cm x 100 cm)	12" W x 17.5" H x 66.8" L (31 cm x 45 cm x 170 cm)	12" W x 11.5" H x 64.25" L (31 cm x 29 cm x 163 cm)
Weight	120 lbs (54.4 kgs)		140 lbs (63.5 kgs)